



	Material Safety Data Sheet	Page: 1
		Revision: 0
		Date: 31.08.09
		Replace :
WATER- AND OIL REPELLENT IMPREGNATING PRODUCT FOR WALLS. CONCRETE, PLASTER AND ROOFS		CARE 1050

1 Identification of the substance/preparation and of the company/undertaking

Trade name: CARE 1050

Use of the substance/preparation: colorless water based impregnating product for walls, concrete, plaster and roofs.

Company: Cormitec bvba
Lageweg 60
8930 Menen
Belgium

Emergency telephone number: +32.(0)9.253 00 87

2 Composition/information on ingredients

Not classified as a hazardous product as per Council Directive 67/548/EEC or 1999/45/EC

Chemical characterisation:

Isopropanol <5 %

CAS nbr: 67-63-0

EG nbr: 200-661-7

Butylglycol <5 %

CAS nbr: 111-76-2

EG nbr: 203-905-0

Fluoropolymers

CAS nbr: not available

Hazardous components:

none

Chemical description:

stabilized clear transparent micro-emulsion in water.

CAS nbrs:

see above

Hazardous impurities:

n.a.

3 Hazards identification

Hazardous components:

Not classified as a hazardous product as per Council Directive 67/548/EEC or 1999/45/EC

Risk phrases:

n.a.



	Material Safety Data Sheet	Page: 2
		Revision: 0
		Date: 31.08.09
		Replace :
WATER- AND OIL REPELLENT IMPREGNATING PRODUCT FOR WALLS. CONCRETE, PLASTER AND ROOFS		CARE 1050

Health hazards: contact irritation of eye and skin, harmful when ingested

Physical and chemical hazards –

Specific hazards:

not known for this concentration

Environmental:

see chapter 12

4 First aid measures

Note to physician:

No hazard which require special First aid measure

First aid:

Inhalation:

There is no danger to inhale the product till 30°C. Respiratory equipment required during spraying.

Skin contact:

Wash with soap and plenty of water. Consult a doctor in the event of a skin reaction. Change badly soiled or soaked clothing

Eye contact:

Remove contact lenses. Immediately wash with plenty of water during several minutes and seek medical advice.

If swallowed:

Rinse mouth, drink lots of water. Contact a physician and show this Safety Data Sheet. DO NOT induce the patient to vomit

Symptoms and effects:

typical symptoms and effects are not known.

Note to physician:

No hazard which require special first aid measures. When large volumes are swallowed, the urine acetone test can be useful.



	Material Safety Data Sheet	Page: 3
		Revision: 0
		Date: 31.08.09
		Replace :
WATER- AND OIL REPELLENT IMPREGNATING PRODUCT FOR WALLS. CONCRETE, PLASTER AND ROOFS		CARE 1050

5 Fire fighting measures

This product is non flammable.

Extinguishing media:

CO₂, foam, dry powder; for larger fires, water spray should be used.

Hazardous combusting products:

In the event of fire, carbon monoxide and carbon dioxide may be released.

Further information:

Do not allow contaminated extinguishing water to enter the soil, ground water or surface waters.

Dispose contaminated extinguishing water in accordance with applicable international, national and local laws, ordinances and statutes.

6 Accidental release measures

Personal precautions:

Wear protective equipment (see Chapter 8)

Environmental precautions

Do not allow to enter the soil, ground water or surface waters.

Methods of cleaning up:

On the ground:

Remove mechanically; cover the remainder with wet, absorbent material (e.g. sawdust, chemical binder based on calcium silicate hydrate, sand).

On water:

formation of a suspension in water, no special requirements.

Neutralization:

n/a

Disposal:

For further disposal measures see Chapter 13.

7 Handling and storage

Handling:

When handling observe the usual precautionary measures for chemicals.

Safe handling advice:



	Material Safety Data Sheet	Page: 4
		Revision: 0
		Date: 31.08.09
		Replace :
WATER- AND OIL REPELLENT IMPREGNATING PRODUCT FOR WALLS. CONCRETE, PLASTER AND ROOFS		CARE 1050

Unusual fire and explosion hazards

Stir and/or shake well before use.
No special requirements.

Storage:

polypropylene, polyethylene and fluoropolymers.

Technical measures:

Store at temperature 5 – 40°C.

Safe storage:

Keep drum tightly closed. Store in a dry area.

To avoid storage conditions:

Avoid frost.

Materials to avoid:

do not store in aluminum, copper, steel, galvanized steel packaging.

Relevant legislation:

No specific recommendations.

8 Exposure controls/personal protection

Protection of workers: indicative Occupational Exposure Limit ValuesIsopropanol

CAS nbr. 67-63-0

Control parameters 3 mg/m³ Time Weighted Average (TWA); (OEL(BE))

Butylglycol

CAS nbr 111-76-2

Control parameters 98 mg/m³ Limit Value Belgium (2002)

Personal protection:**Respiratory:**

Respiratory equipment required during spraying.

Hands:

Wear rubber or PVC gloves

Eyes:

Wear eye/face protection.

Skin:

Wear suitable protective clothing.



	Material Safety Data Sheet	Page: 5
		Revision: 0
		Date: 31.08.09
		Replace :
WATER- AND OIL REPELLENT IMPREGNATING PRODUCT FOR WALLS. CONCRETE, PLASTER AND ROOFS		CARE 1050

Hygienic precautions:

Do not eat, drink or smoke during use of the product.

Wash hands before breaks and at end of work.

Keep working clothes separate.

Change badly soiled or soaked clothing.

9 Physical and chemical properties

Appearance:	liquid
Color:	colorless, slightly yellow
Odor:	weak odour
pH:	neutral, 6,5 – 7,5
Freezing point (°C):	-3° C
Stability:	3 °C tot 40 °C
Application temperature:	15° C tot 35 °C
Melting point (°C):	-3° C
Boiling point (°C):	100 °C
Decomposition temperature (°C):	n/a
Specific gravity (Kg/dm³):	0,991
Relative density against water:	n/a
Bulk density (Kg/m³):	n/a
Vapour pressure (kPa):	cf. Water
Solubility in water (g/ 100 ml):	water based emulsion
Flash point (°C):	49 °C
Auto flammability (°C):	n/a
Explosion limits %	n/a
- lower (°C):	n/a
- upper (°C):	n/a
Evaporation rate:	cf. Water
Oxidizing properties:	cf. Water
Specific conductivity (S/m):	cf. Water

10 Stability and reactivity

Stability:	Stable under normal conditions
Hazardous reactions:	not known
Conditions to avoid:	Always close container tightly after removal of product. Avoid frost.



	Material Safety Data Sheet	Page: 6
		Revision: 0
		Date: 31.08.09
		Replace :
WATER- AND OIL REPELLENT IMPREGNATING PRODUCT FOR WALLS. CONCRETE, PLASTER AND ROOFS		CARE 1050

Materials to avoid: materials which corrodes with water.
Hazardous decomposition: Carbon monoxide, carbon dioxide (CO₂).

11 Toxicological information

Acute oral toxicity: LD50 rat: >4000 mg/kg ingestion of large amount of product can cause stomach ache, diarrhoea, sickness.
 Method: calculation.

Skin irritation: irritating at long term exposure.

Eye irritation: irritating.

Inhalation: not irritating with normal use and temperature.

Carcinogenic: Non of the products are listed as carcinogenic.

12 Ecological information

Elimination information (persistence and degradability)

Behavior in environmental compartments

Ecotoxicity effects

Isopropanol, CAS nbr: 67-63-0 en Butylglycol, CAS nbr: 111-76-2 are volatile organic substances in accordance with EC Directives 1999/13/EG and are completely water soluble. Low water polluting product.

Care 1050 is good biodegradable and water soluble. No expected bioaccumulation at these concentrations.

Concentrates: isopropanol LC50 (24h) daphnia: >1000 ppm; butylglycol LC50 (24h) daphnia: >100 ppm.

13 Disposal considerations

Disposal of residue/unused products:

Dispose in accordance with applicable international, national and local laws, ordinances and statutes.

For disposal within the EC, the appropriate code according to the European Waste Catalogue (EWC) should be used.



	Material Safety Data Sheet	Page: 7
		Revision: 0
		Date: 31.08.09
		Replace :
WATER- AND OIL REPELLENT IMPREGNATING PRODUCT FOR WALLS. CONCRETE, PLASTER AND ROOFS		CARE 1050

After containers have been emptied as thoroughly as possible (e.g. by pouring, scraping or draining until 'drip-dry'), they can be sent to an appropriate collection point set up within the framework of the existing take-back scheme of the chemical industry.

Containers must be recycled in compliance with national legislation and environmental regulations.

14 Transport information

Transport :

The product is not classified as dangerous goods.
RID/ ADR Class: n/a

15 Regulatory information

No labelling is required for this material by the Chemicals (Hazard Information and Packaging for Supply) Regulations 2002 (CHIP3), in accordance with EC' Directives

Trade name:	CARE 1050
Symbols:	none
R-phrases:	none
S-phrases:	none
Basis of the classification:	n/a
EG-Annex N:	n/a

16 Other information

Page VIB:	right corner, first line
Revision VIB:	right corner, second line
Revision date:	right corner, third line
Date previous revision:	right corner, fourth line
Writer:	Didier Desschans
Revised parts:	changes with reference to previous versions are market with "#".
Information sources:	Original VIB and specifications from manufacturers.

Further information

This version replaces all previous versions.



	Material Safety Data Sheet	Page: 8
		Revision: 0
		Date: 31.08.09
		Replace :
WATER- AND OIL REPELLENT IMPREGNATING PRODUCT FOR WALLS. CONCRETE, PLASTER AND ROOFS	CARE 1050	

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.